

ADPRO - ADHESION PROMOTER FOR PLASTIC SURFACE

Adhesion of PU Paint directly on Plastic substrate is not good. To improve the adhesion of PU Paint on plastic we recommend application of our ADPRO directly on Plastics substrate followed by PU Topcoats.

AREAS OF APPLICATION:

Plastic bumpers, plastic dash boards on any other plastic component of a vehicle.

SURFACE PREPARATION:

In case of unpainted bumpers or dashboards, wash with water, containing good quality of detergent. Allow to dry thoroughly. Then clean with any solvent for removing any stain of oil or grease. Again, allow the solvent to evaporate totally.

DIRECTIONS FOR USE:

Prepare the surface as directed earlier and spray 2 thin coats, wet on wet, of ADPRO. Allow to dry for two hours and spray 2 coats of Maridur PU Paint. shade.

NOTES:

ADPRO will help in adhesion of PU paints only.



ADPRO Technical Data

Appearance	: Pale yellow.
Viscosity	: 14 - 15 seconds in FC/4@ 30o C.
Weight/litre	: 0.86 kg.
Drying time	: Touch dry : 5 minutes Tack free : 20 – 25 minutes
Overcoatability	: TWO HOURS
Dry film thickness	: 7 – 10 microns